



# DOCSIS 3.1 Cable Modem

with Switchable Frequency

CODA-47



With support for DOCSIS 3.1 (download speeds up to 10 Gbps\*), residential and business customers will enjoy the ultimate digital experience, today and tomorrow, with richer ultra-HD video streaming, faster online gaming, virtual reality applications, more reliable video conferencing and more. And two GigE ports provide the fastest wired speeds to connect a Wi-Fi router, computer or other wired device.

## DOCSIS 3.1 Certified


DOCSIS 3.1 takes Internet speeds to a new level, increasing the capacity of HFC networks by more than 50 percent and reducing latency. This means your customers can connect more devices, enjoy richer digital experiences, and get fast, reliable Internet service for all of today and tomorrow's needs.

## Easy to Setup and Manage

Installation is a snap for your end users. The built-in TFTP client automatically gets the IP address and configuration data from the network server. That means a few simple connections is all it takes to get up and running. And SNMP support provides total remote control over the device for fast and effective troubleshooting.

## Key Features

- DOCSIS 3.1 2x2 OFDM/OFDMA
- DOCSIS 3.0 32x8 Channel Bonding
- Switchable 5-85/5-204MHz
- Two 1 GigE Ports
- Built-in MoCA Immunity Filter
- Supports Business Services over DOCSIS



## Interfaces

- 1x RF F-Type 75Ω Female Connector
- 2x RJ-45 10/100/1000BASE-T Ethernet Ports

## Reception-Demodulation

- DOCSIS 3.1/3.0/2.0
- DOCSIS 3.1 Demodulation: Multi-carrier OFDM 16 to 4096QAM
- DOCSIS 3.1 Data Rate: Up to 10Gbps with 2 OFDM 192MHz Downstream Channels + 32 SC-QAM
- DOCSIS 3.0 Demodulation: 64QAM, 256QAM
- DOCSIS 3.0 Data Rate: Up to 1.2Gbps with 32 Bonded Downstream Channels
- Frequency (edge-to-edge): 258-1002MHz
- Channel Bandwidth: 6MHz
- Signal Level: 15dBmV

## Transmitter-Modulation

- DOCSIS 3.1/3.0/2.0
- DOCSIS 3.1 Modulation: Multi-carrier OFDMA BPSK to 4096QAM
- DOCSIS 3.1 Data Rate: Up to 1 Gbps with OFDMA 96MHz Upstream Channels
- DOCSIS 3.0 Modulation: QPSK, 8QAM, 16QAM, 32QAM, 64QAM, and 128QAM (SCDMA only)
- DOCSIS 3.0 Data Rate: Up to 320Mbps with 8 bonded Upstream Channels
- Frequency: Switchable 5-85/ 5-204MHz
- Upstream Transmit Signal Level: +11 to 65dBmV

## Management

- Protocol Support: TFTP, SSHv2, SNMP v2, v3
- Web-based GUI Control, Configuration and Management
- Power-on Self-Diagnostic
- Hitron-proprietary MLBs for Extended Support on DOCSIS

## Mechanical

- LEDs: 5 (Power, DS, US, Status, LAN)
- Factory Default Reset Button
- Dimensions: 51.5mm (H) x 171mm (W) x 171mm (D)
- Net Weight: 464 +/- 10g

## Electrical

- Input Power: 12VDC, 2A
- Power Adaptor: 100-240VAC, 50/60Hz
- Power Consumption: xxxW (power saving), 15W (typ.), xxxW (Max)
- Surge Protection
  - RF Input sustains at least 4KV
  - Ethernet RJ-45 sustains at least 4KV

## Environmental

- Operating Temperature: 0°C (32°F) ~ 40°C (104°F)
- Operating Humidity: 10% ~ 90% (Non-condensing)
- Storage Temperature: -40°C (-40°F) ~ 60°C (140°F)

## Regulatory Compliance

- RoHS
- CableLabs
- FCC Part 15 Class B Subpart B, Part 15.247, Part 15.407, Part 2.1091
- ICES-003 Issue 6, Class B
- RSS-102 Issue 5
- IC RSS-247 Issue 2, 2017-02 and RSS-Gen Issue 5, 2018-4
- Canada RSS-Gen Issue 5, Amendment 1, Mar 2019
- UL 62368-1
- cUL 62368-1-14



1.TV F219020